

VIN:

Vehicle:

System Version:

Data Version:

00 41 13 (045)

Maintenance work, MINI F56

Situation:

On the MINI F56, the due services are always displayed in the Condition Based Service (CBS).

Calculation of the remaining distance and therefore the CBS display for the front and rear brake service are discontinued. The remaining brake pad thickness must be measured manually at every service visit.

Service work carried out must be copied to the vehicle's electronic service history.

Vehicles concerned: MINI F56

Procedure:

Intervals as stated here refer only to the ECE basic interval.

Country specific deviations may apply. For countries with lower-quality fuel grades, comply with the [country-specific intervals](#).

Carry out standard scope of service work for each service:

New check point:

- Check brake pad thickness on the front axle and rear axle.

Carry out **engine oil change service** roughly every 30,000 km/24 months.

Change intervals that are linked with the engine oil service:

- Microfilter => replace at every engine oil change (approx. 30,000 km)
- Air filter => replace every 2nd engine oil change (approx. 60,000 km)
- Petrol models:
Spark plugs => replace every 2nd engine oil change (approx. 60,000 km)
- Diesel models:
Fuel filter => replace every 2nd engine oil change (approx. 60,000 km)

Carry out vehicle check service roughly every 60,000 km/48 months (every second engine-oil service).

Carry out scopes of checks according to the maintenance schedule:

Carry out a **brake fluid service** after 36 months and subsequently every 24 months.

New check point for vehicles with active pedestrian protection system (SA8TF):

- Check expiry date on gas pressure spring of engine compartment lid. Expiry must last until the next brake fluid service!

Replace gas pressure spring, if necessary. The replacement is subject to a separate charge.

Front/rear brake service

Reset of the CBS display is discontinued.